

Electrolux 220-300 G-force Washers

X-Series, Extra Spin for Coin/Card

Heavy-duty, built to last, and saves up to 50% on water – automatically.

Electrolux Professional 220-300 G-Force high-speed extraction, solid-mount washers minimize drying time and provide significant electrical and gas savings. Self-service laundries benefit from faster throughput (freeing up dryers, folding tables and parking spots) which creates higher profits. Your customers can even receive a text message (option) notifying them when their wash is done and ready for unloading! Increase your profits and create customers for life with the unique features of Electrolux Professional washers. Electrolux X-Series washers are built to take the abuse of a demanding coin laundry environment and to provide years and years of trouble-free operation.

FEATURES AND BENEFITS:

- AS (Automatic Savings) - saves up to 50% on water. With every wash cycle, AS determines the actual weight of the load and adds precisely the right amount of water significantly reducing water consumption and energy costs (available on 65 & 80 lb. models)
- Extremely low water and energy consumption
- Convenient four compartment detergent box
- Large, secure coin box
- 220-300 G-force extraction removes more water, saving energy & time in dryer
- Heavy-duty construction with robust steel door and lock, hinges set wide apart
- Stainless and galvanized steel in all vital parts for maximum rust protection
- Power Balance ensures the correct extraction and maximum savings in drying time. Minimizes stress on machines for trouble free operation and longer machine life.
- Sanitizing Rinse for greater customer satisfaction and additional revenue
- Text messaging - option
- Voice guidance - option

COMPASS PRO MICROPROCESSOR OFFERS:

- Easy to customize programs
- Large display and one control knob for easy program selection
- More than 20 languages available – displays two languages, simultaneously
- Real time clock for time of day pricing, happy hour pricing and promotions
- Heavy Soil and Extra Rinse option buttons for higher customer satisfaction and increased revenue
- Detailed user statistics and programmability



Available in 65, 80, and 135 lb. capacities.
The 135 lb model does NOT have AS.



Designed by experts. Inspired by you.

Electrolux "X" Models, 300G	W5280X		W5350X		W5600X	
Capacity (lb/kg)	65	30	80	36	135	60
Width (in/mm)	36 3/4	933	43 7/8	1115	46 3/16	1173
Depth (overall) (in/mm)	38 3/4	985	44 1/8	1121	50 5/8	1286
Height (in/mm)	57 5/16	1456	61 13/16	1570	65 7/8	1673
Height to bottom of door (in/mm)	20 1/2	520	21	534	21 1/4	540
Door opening diameter (in/mm)	16 1/8	410	21 1/16	535	21 1/16	535
Cylinder volume (ft ³ /l)	9.9	280	12.4	350	21.2	600
Drain outlet diameter (in/mm)	2 15/16	75	2 15/16	75	2 15/16	75
Height to centerline of drain (in/mm)	4 11/16	119	4 13/16	122	4 1/16	103
Extract (rpm/G-Force)	805 / 300		650 / 220		630 / 220	
Dynamic floor load (lb/kN)	1101 +/- 2135	4.9 +/- 9.5	1551 +/- 2405	6.9 +/- 10.7	2248 +/- 3507	10 +/- 15.6
Dynamic frequency (Hz)	13.4		10.8		10.5	
Noise level (dBA) in extraction	<75		<82		<84	
Crated width - (in/mm)	43 5/16	1100	44 7/8	1140	47 5/8	1210
Crated depth - (in/mm)	45 11/16	1160	54 5/16	1380	55 1/8	1400
Crated height - (in/mm)	62 5/8	1590	67 11/16	1720	72 13/16	1850
Crated weight (lb/kg)	882	401	1272	579	1920	873
Electrical Requirements (standard)						
Voltage/frequency/phase	208-240/60/1 or 3 ~		208-240/60/1 or 3 ~		208-240/60/3~	
Power (kW) / Full-load current (A) / Ckt breaker (A)	1.5 / 7.2 / 15		1.8 / 8.6 / 15		2.6 / 7.2 / 15	
Voltage/frequency/phase	480 / 60 / 1 or 3~		480/60/1 or 3~		480/60/3~	
Power (kW) / Full-load current (A) / Ckt breaker (A)	1.5 / 3.1 / 10		1.8 / 3.8 / 10		2.6 / 3.1 / 10	
Water Information						
Inlet fittings (* = 3 inlets)	3/4"	DN20	3/4"	DN20	1"	DN25
Flow (gpm/lpm @ 45 psi) (each inlet)	16	60	16	60	25	110
Recommended water pressure (psi/kPa)	30 - 90	200-600	30 - 90	200-600	30 - 90	200-600
Approx Water usage (gal / liters @ full load)						
Modified Energy Factor	n/a					
Water Factor (Gal per cycle/drum volume)						
<p>Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, common-trip, circuit breakers ONLY. Warranty void if not properly installed. Solid-mount machines require a concrete foundation, and are not suitable for upper-floor or above-basement installations. Contact us for more information and for availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.</p>						



Electrolux Professional Line 5000 The all-in-one business solution for your self-service laundry.



Greatest flexibility with Compass Pro*

- Real-time clock for time-of-day and happy hour pricing
- Multi-language menu selection
- Easy to customize
- Simple to use
- Revenue generating option buttons



Extended lifetime due to Super Balance / Power Balance™

- Lower maintenance costs
- Less vibration
- Maximum water extraction
- Lower energy costs



Cost savings in water & energy with Automatic Savings (AS)

- Determines load weight and adds precisely the correct amount of water
- Up to 50% water savings - automatically
- Reduces water and energy consumption



Ontario
Laundry Systems Inc.

Proudly Canadian. Family owned and operated since 1995.

7475 Kimbel St, Unit 5 • Mississauga, ON L5S 1E7
905-673-1308 • info@ontariolaundry.com • ontariolaundry.com